



### KECK RELEASE AGENT 1602/18

KECK Release -Agent are composed as ready for use Release-Agents that are to be processed with specially modified spraying equipment. As result of our experiences, the following spraying equipments are suitable:

1. manual processing: Keck-Spraying-Equipment, specially modified for spraying of KECK-Release-Agent.
2. automatic processing: Release-Agent-Spraying-Robot

#### Application:

KECK-Release-Agent 1602/18 is a special development suitable for the demoulding of working shoes which are directly soled with polyether foams and are mainly worn in the automobile industry.

This Release-Agent is composed on base of synthetic oils.

It distinguishes through a very mat surface as well as pleasant grip. During processing of KECK Release-Agent 1602/18 there has to be paid attention to the fact that the material will be stirred or circulated very well.

#### Operating Instructions:

The Release-Agent may be pulverized with KECK-Spraying-Equipment, specially modified for KECK Release-Agent. This system represents a closed system. Please take care for a material-pressure of 0.2 - 0.4 bar and a processing-pressure of 1 bar for the spraying gun and a nozzle size of 0.3 mm.

A fully developed spraying technique which is represented through the system elaborated by KECK is very important for the usage of KECK-Release-Agent. Only through this it is guaranteed that the demoulded soles have a perfect look concerning the quality and furthermore an optimal processing of the Release-Agent is granted due to this spraying system.

#### Technical Data:

Base:	synthetic oils
Density:	0,872 kg/ltr
Hazardous Classification:	A 2
Flash-Point:	36°C
Storage:	cool and dry

2012

The information contained herein is based on our technical knowledge and experience. Since it is the user's responsibility to determine the suitability of the product for his own use, he should thoroughly test any application. In the bounds of our delivery terms we grant constant quality.