

SAHARA Fabrics for reinforcement

Product (without adhesive layer)	Weight (g/m²)	Thickness (mm)	Adhesive (on request)
SAHARA 05	245 - 305	0.45 - 0.55	OS/OT6
SAHARA 07	345 - 425	0.65 - 0.75	OS/OT6
SAHARA 09	445 - 545	0.85 - 0.95	OS/OT6
SAHARA 12	590 - 730	1.15 - 1.25	OS/OT6
SAHARA 15	740 - 910	1.45 - 1.55	OS/OT6

Adhesive nature (on one side)
OS (self-adhesive)
OT6 (film thermoadhesive eva based with high adhesion)



Technical Features

SAHARA fabrics are produced through a special treatment of synthetic fibres with NBR latexes.

Reinforcement fabrics of **SAHARA** series are realized for specific applications in leather goods and shoes production.

In leather goods, **SAHARA** is particularly useful also for coupling thin leathers.

Its main property is fabric high density that lead to a soft hand suitable for several kind of applications.

SAHARA is available in three different colours: white, charcoal grey, sandy.



Mode of use

In the case of versions with thermoadhesive **OT6**, **SAHARA** must be pressed with heated press at 80-130°C, pressure of 3-4 atm and for 4-6 seconds (in relation to the type of leather).

The self-adhesive version **OS** is suitable for those who need simple positioning before sewing.

SAHARA 05 in rolls of linear meters in H. 150 cm (50 linear meter)

SAHARA 07 in rolls of linear meters in H. 150 cm (33 linear meter)

SAHARA 09 in rolls of linear meters in H. 150 cm (33 linear meter)

The information contained herein is based on our technical knowledge and experience. Since it is the user's responsibility to determine the suitability of the product for his own use, he should thoroughly test any application.